

## Yield Reporting Form: HP LaserJet 4100 cartridge model C8061X

Declared ISO yield

<p><b>Toner cartridge yield:</b></p> <p style="text-align: center;">Average cartridge yield 10,000 standard pages<sup>1</sup></p> <p style="text-align: center;"><i>Declared yield value in accordance with ISO/IEC 19752 based on continuous printing</i></p>
--

Calculated test values

Average <sup>1</sup>	10,298
Standard Dev.	475
90% lower confidence limit <sup>1</sup>	10,132

Test date: beginning	7/16/2013
Test dates: ending	7/29/2013
Number of cartridges used in testing	24
Number of cartridges used in calculations	24
Type of cartridge	Hewlett Packard C8061X all in one
Shake procedure used?	No
Print mode	Continuous
Job size	500 pages per job
Number of engines used in testing	4
Media	HP Multipurpose
Paper size	Letter
Paper feed orientation	Short edge
Computer model	vSphere Client virtual PC
Operating system	Microsoft Windows XP Pro with SP3
Application software	Adobe Reader 6
Print driver version	HP Laser Jet 4100 PCL6
Connection type	network
Test page version*	Version 4.0 pdf

Power on/off every day	No
------------------------	----

Engine serial numbers:	Engine Firmware Version:
Unknown	20010315 01.013.0
USBDC00553	20030729 01.040.2
USBDF04320	20030729 01.040.2
USJNF14185	20020723 01.034.0

\*filename: Download\_Free\_\_\_19752\_Test\_Chart\_\_.pdf from ISO SC28 website

Cartridge testing data

Test environmental limits:	Temperature	Humidity
	°C	%RH
Max running average	22.9	53
Min running average	22.6	51
Average	22.7	52

<b>C8061X</b>		<b>LJ 4100</b>	
<b>Cartridge</b>	<b>Lot Code</b>	<b>Engine SerNo</b>	<b>Cartridge Yield</b>
C8061X-010	3C15H7a	Unknown	10190
C8061X-011	3E24H7a	USBDC00553	11068
C8061X-012	3C15H7a	USBDF04320	10244
C8061X-013	3E24H7a	USJNF14185	10493
C8061X-014	3D19H7a	Unknown	10952
C8061X-015	3A24H7a	USBDC00553	9580
C8061X-016	3D19H7a	USBDF04320	10152
C8061X-017	3A24H7a	USJNF14185	9403
C8061X-018	3E24H7a	Unknown	10941
C8061X-019	3C15H7a	USBDC00553	10910
C8061X-020	3E24H7a	USBDF04320	10028
C8061X-021	3C15H7a	USJNF14185	10659
C8061X-022	3A24H7a	Unknown	10371
C8061X-023	3D19H7a	USBDC00553	10598
C8061X-024	3A24H7a	USBDF04320	9423
C8061X-025	3D19H7a	USJNF14185	10460
C8061X-026	3C15H7a	Unknown	10334
C8061X-027	3E24H7a	USBDC00553	10741
C8061X-028	3C15H7a	USBDF04320	10355
C8061X-029	3E24H7a	USJNF14185	10386
C8061X-030	3D19H7a	Unknown	10086
C8061X-031	3A24H7a	USBDC00553	10291
C8061X-032	3D19H7a	USBDF04320	9866
C8061X-033	3A24H7a	USJNF14185	9620

<sup>1</sup> In an ISO report two values are commonly listed: declared ISO yield and calculated test values. Generally, the calculated test values are higher than the declared ISO yield. Actual cartridge yields vary considerably based on content of images printed and other factors. For more information visit [www.hp.com/go/learnaboutsupplies](http://www.hp.com/go/learnaboutsupplies).