

### Date: 24 January 2018

#### Voluntary Accessibility Template (VPAT)

This Voluntary Product Accessibility Template (VPAT) describes accessibility of Polycom's Unified Conference Station PC Admin Application against the criteria described in Section 508 of the United States Rehabilitation Act of 1973, as amended (29 U.S.C. 794d). The template format is intended to permit easy evaluation of conformance to Section 508

<u>Name of Product</u>: Polycom® Business IP Phones (VVX150, VVX250, VVX350, VVX450, Expansion Module EM50) and UC Software (version UCS 5.8.0)

Company contact for more Information: Ian Jennings, ian.jennings@polycom.com

<u>Note:</u> This document describes normal operational functionality. It does not include maintenance and troubleshooting procedures.

<u>Note:</u> This document uses the accessibility criteria described in the Revised Section 255 Guidelines of January 2017.

#### SUMMARY TABLE

#### VOLUNTARY PRODUCT ACCESSIBILITY SUMMARY

Section	Criteria	Supporting Features	Remarks and explanations
Chapter	3 Functional Performance Criteria		
301	General	Exceptions	
302	Functional Performance Criteria	Exceptions	
Chapter	4 Hardware		
401	General	Supports	
402	Closed Functionality		
403	Biometrics		
404	Preservation of Accessibility Information	Support	
405	Privacy	Supports	
406	Standard Connections	Supports	
407	Operable Parts	Exceptions	
408	Display Screens		
409	Status Indicators	Supports	
410	Color Coding	Supports	
411	Audible Signals	Supports	
412	ICT with Two-Way Voice Communication	Supports	
413	Closed Caption Processing Technologies		
414	Audio Description Technologies		
415	User Control for Captions and Audio Descriptions		
Chapter	5 Software		
501	General		
502	Interoperability with Assistive Technology		
503	Applications		
504	Authoring Tools		
Chapter	6 Support Documentation/Services.		
601	General	Supports	
602	Support Documentation	Supports	
603	Support Services	Supports	

# Appendix C to Part 1194 – Functional Performance Criteria and Technical Requirements

### **Chapter 3: Functional Performance Criteria**

# **301** General

301.1 Scope. The requirements of Chapter 3 shall apply to ICT where required by 508 Chapter 2 (Scoping Requirements), 255 Chapter 2 (Scoping Requirements), and where otherwise referenced in any other chapter of the Revised 508 Standards or Revised 255 Guidelines.

#	Criteria	Supports	Comments
302.1	Without Vision.		
	Where a visual mode of operation is provided, ICT shall provide at least one mode of operation that does not require user vision.	Supports with Exception	Audible ring and alert tones. Dial pads on Polycom phones are arranged in a standard twelve-button layout with the conventional raised area on the "5" button. Buttons follow a consistent arrangement across different phones in the product line, to facilitate navigation by touch.
302.2	With Limited Vision.		
	Where a visual mode of operation is provided, ICT shall provide at least one mode of operation that enables users to make use of limited vision.	Supports	All Polycom VVX phones have a level of contrast adjustment to increase the brightness of the display. Dial pads on Polycom phones are arranged in a standard twelve-button layout with the conventional raised area on the "5" button. Buttons follow a consistent arrangement across different phones in the product line, to facilitate navigation by touch. The device is also compatible with optical and electro-optical assistive technology such as magnifying glasses and image magnification systems.
302.3	Without Perception of Color.		
	Where a visual mode of operation is provided, ICT	Supports	Icons are used to provide indication of state (such as DND) as well as color.

#### **302** Functional Performance Criteria

All contents copyright © 2018 Polycom, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the date above.

	shall provide at least one visual mode of operation that does not require user perception of color.		Skype for Business Presence state is given both textually and via color.
302.4	Without Hearing.		
	Where an audible mode of operation is provided, ICT shall provide at least one mode of operation that does not require user hearing.	Not Applicable	

302.5	With Limited Hearing.		
	Where an audible mode of	Supports	Although exchange of information via
	operation is provided, ICT		audio is the primary purpose, audio
	shall provide at least one		information is not required to operate
	mode of operation that		the product, other than the ring tone.
	enables users to make use of		For alerting calls, a visual display is
	limited hearing.		provided as well as user defined ring
			tones. TTY support is available enhance
			the audio required for users who are
			hard of hearing. Any control action that
			is required by the phone is handled via
			keypad or touch screen. Speech control
			is not required to operate this product.
302.6	Without Speech.		
	Where speech is used for	Not Applicable	
	input, control, or operation,		
	ICT shall provide at least one		
	mode of operation that does		
	not require user speech.		
302.7	With Limited Manipulation.	-	
	Where a manual mode of	Supports	Physical operation does not require fine
	operation is provided, ICT		motor control or simultaneous actions.
	shall provide at least one		
	mode of operation that does		
	not require fine motor		
	control or simultaneous		
	manual operations.		
302.8	With Limited Reach and Stren		F
	Where a manual mode of	Supports	The unit can be moved to a position
	operation is provided, ICT		where limited reach will not be a
	shall provide at least one		restriction.
	mode of operation that is		Limited strength is also not a
	operable with limited reach		restriction.
	and limited strength.		
302.9	With Limited Language, Cogni		
	ICT shall provide features	Supports	Iconography on the display and on the
	making its use by individuals		keys enable the ICT to be more intuitive
	with limited cognitive,		to operate when compared with text
	language, and learning		strings.
	abilities simpler and easier.		

# **CHAPTER 4: HARDWARE**

# 401 General

401.1 Scope. The requirements of Chapter 4 shall apply to ICT that is hardware where required by 508 Chapter 2 (Scoping Requirements), 255 Chapter 2 (Scoping Requirements), and where otherwise referenced in any other chapter of the Revised 508 Standards or Revised 255 Guidelines.

# 402 Closed Functionality

#	Criteria	Supports	Comments
40	02.1 General.		
	ICT with closed functionality shall	Not Applicable	
	be operable without requiring the		
	user to attach or install assistive		
	technology other than personal		
	headsets or other audio couplers,		
	and shall conform to 402.		
40	02.2 Speech-Output Enabled.	r	
	ICT with a display screen shall be	Not applicable	
	speech-output enabled for full and		
	independent use by individuals		
	with vision impairments.		
	EXCEPTIONS:		
	1. Variable message signs		
	conforming to 402.5 shall not be		
	required to be speech-output		
	enabled.		
	2. Speech output shall not be		
	required where ICT display screens		
	only provide status indicators and		
	those indicators conform to 409.		
	3. Where speech output cannot be		
	supported due to constraints in		
	available memory or processor		
	capability, ICT shall be permitted to		
	conform to 409 in lieu of 402.2.		
	4. Audible tones shall be permitted		
	instead of speech output where		
	the content of user input is not		
	displayed as entered for security		
	purposes, including, but not limited		
	to, asterisks representing personal		
	identification numbers.		

All contents copyright © 2018 Polycom, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the date above.

	5. Speech output shall not be		
	required for: the machine location;		
	date and time of transaction;		
	customer account number; and the		
	machine identifier or label.		
	6. Speech output shall not be		
	required for advertisements and		
	other similar information unless		
	they convey information that can		
	be used for the transaction being		
	conducted.		
4	02.2.1 Information Displayed On-Scr	een.	
	Speech output shall be provided	Not Applicable	
	for all information displayed on-		
	screen.		
4	02.2.2 Transactional Outputs.		
	Where transactional outputs are	Not Applicable	
	provided, the speech output shall		
	audibly provide all information		
	necessary to verify a transaction.		
4	02.2.3 Speech Delivery Type and Coor	rdination.	
	Speech output shall be delivered	Not Applicable	
	through a mechanism that is		
	readily available to all users,		
	including, but not limited to, an		
	industry standard connector or a		
	telephone handset. Speech shall be		
	recorded or digitized human, or		
	synthesized. Speech output shall		
	be coordinated with information		
	displayed on the screen.		
4	02.2.4 User Control.		
	Speech output for any single	Not Applicable	
	function shall be automatically		
	interrupted when a transaction is		
	selected. Speech output shall be		
	capable of being repeated and		
	paused.		
4	02.2.5 Braille Instructions.		
	Where speech output is required	Not Applicable	
	by 402.2, braille instructions for		

			Ι
	initiating the speech mode of		
	operation shall be provided. Braille		
	shall be contracted and shall		
	conform to 36 CFR part 1191,		
	Appendix D, Section 703.3.1.		
	EXCEPTION: Devices for personal		
	use shall not be required to		
	conform to 402.2.5.		
40	02.3 Volume.		
	ICT that delivers sound, including	Not Applicable	VVX phones have volume control
	speech output required by 402.2,		functionality to control the volume
	shall provide volume control and		speech output via handset, headset or
	output amplification conforming to		speaker phone.
	402.3.		
	<b>EXCEPTION</b> : ICT conforming to		
	412.2 shall not be required to		
	conform to 402.3.		
10	02.3.1 Private Listening.		
	Where ICT provides private	Not Applicable	All Polycom handsets are designed to
	listening, it shall provide a mode of		support acoustic TTY coupling.
	operation for controlling the		Volume control is provided through a
	volume. Where ICT delivers output		hardware button.
	by an audio transducer typically		
	held up to the ear, a means for		
	effective magnetic wireless		
	coupling to hearing technologies		
	shall be provided.		
40	2.3.2 Non-private Listening.		
	Where ICT provides non-private	Not Applicable	
	listening, incremental volume		
	control shall be provided with		
	output amplification up to a level		
	of at least 65 dB. A function shall		
	be provided to automatically reset		
	the volume to the default level		
	after every use.		
40	02.4 Characters on Display Screens.		
	At least one mode of characters	Not Applicable	All text on the display will use San Serif
	displayed on the screen shall be in		fonts.
	a sans serif font. Where ICT does		
40	<b>2.4 Characters on Display Screens.</b> At least one mode of characters displayed on the screen shall be in	Not Applicable	

	not provide a screen enlargement feature, characters shall be 3/16 inch (4.8 mm) high minimum based on the uppercase letter "I". Characters shall contrast with their background with either light characters on a dark background or dark characters on a light background.		
4	02.5 Characters on Variable Message	Signs.	
	Characters on variable message signs shall conform to section 703.7 Variable Message Signs of ICC A117.1-2009 (incorporated by reference, see 702.6.1).	Not Applicable	

### **403 Biometrics**

#	Criteria	Supports	Comments
4	03.1 General.		
	Where provided, biometrics shall not be the only means for user identification or control.	Not Applicable	VVX phones will not use biometrics for authentication.
	<b>EXCEPTION</b> : Where at least two biometric options that use different biological characteristics are provided, ICT shall be permitted to use biometrics as the only means for user identification or control.		

### 404 Preservation of Information Provided for Accessibility

#	Criteria	Supports	Comments	
4	404.1 General.			
	ICT that transmits or converts information or communication shall not remove non-proprietary information provided for accessibility or shall restore it upon delivery.	Supports	VVX phones do not modify or remove any information that is to be sent.	

# 405 Privacy

# Criteria	Supports	Comments	
405.1 General.			
The same degree of privacy of input and output shall be provided to all individuals. When speech output required by 402.2 is enabled, the screen shall not blank automatically.	Supports	The screen on VVX phones is never blanked during operation.	

### **406 Standard Connections**

#	Criteria	Supports	Comments	
4	406.1 General.			
	Where data connections used for	Supports	Phones use RJ9 style connectors for	
	input and output are provided, at		headsets and standard Ethernet for	
	least one of each type of		network connectivity. USB ports (where	
	connection shall conform to		included) are standards based full sized	
	industry standard non-proprietary		USB ports	
	formats.			

### **407 Operable Parts**

#	Criteria	Supports	Comments
40	07.1 General.		
	Where provided, operable parts used in the normal operation of ICT shall conform to 407.	Supports	
40	07.2 Contrast		
	Where provided, keys and controls shall contrast visually from background surfaces. Characters and symbols shall contrast visually from background surfaces with either light characters or symbols on a dark background or dark characters or symbols on a light background.	Supports	Standard color scheme for the phones is to use white text/images on dark grey/black buttons. On the UI we maintain at least 85% contrast ratio between foreground text and the background color.

407.3 Input Controls		
	Supports	1
At least one input control	Supports	
conforming to 407.3 shall be		
provided for each function.		
<b>EXCEPTION:</b> Devices for personal		
use with input controls that are		
audibly discernable without		
activation and operable by touch		
shall not be required to conform to		
407.3.		
407.3.1 Tactilely Discernable		
Input controls shall be operable by	Supports	Polycom VVX products have a
touch and tactilely discernible		distinctive raised pattern on the "5" key
without activation.		that will allow users to identify which
407.3.2		key they are pressing in relation to the
		"5" key along with raised patterns on
		the navigation keys.
407.3.2 Alphabetic Keys		
Where provided, individual	Not Applicable	
alphabetic keys shall be arranged		
in a QWERTY-based keyboard		
layout and the "F" and "J" keys		
shall be tactilely distinct from the		
other keys.		
407.3.3 Numeric Keys		1
Where provided, numeric keys	Supports	Polycom VVX products have a
shall be arranged in a 12-key		distinctive raised pattern on the "5" key
ascending or descending keypad		that will allow users to identify which
layout. The number five key shall		key they are pressing in relation to the
be tactilely distinct from the other		"5" key. The arrangement of phone
keys. Where the ICT provides an		keys is in compliance with ITU-T
alphabetic overlay on numeric		Recommendation E.161 with the
keys, the relationships between		exception that two raised dots are
letters and digits shall conform to		provided rather than the single dot as
ITU-T Recommendation E.161		specified in section 3.6 of ITU-T
		Recommendation E.161.
(incorporated by reference, see		
702.7.1).		
407.4 Key Repeat	Not Applicable	Kouhoard doos not support kou repost
Where a keyboard with key repeat is provided, the delay before the		Keyboard does not support key repeat.
is provided, the delay before the		

All contents copyright © 2018 Polycom, Inc. All rights reserved.

This information is true and correct to the best of our knowledge as of the date above. This information is supplied for market research purposes only, and is subject to change without notice. The contents of this document do not constitute legal advice, representation, warranty or guarantee regarding the products described, and make no claims regarding anyone's ability to comply with applicable accessibility requirements. Such a determination is the sole responsibility of the purchaser.

k	ey repeat feature is activated shall	
b	e fixed at, or adjustable to, 2	
S	econds minimum.	

40	407.5 Timed Response			
	Where a timed response is	Not Applicable		
	required, the user shall be alerted			
	visually, as well as by touch or			
	sound, and shall be given the			
	opportunity to indicate that more			
	time is needed.			
40	07.6 Operation			
	At least one mode of operation	Supports	No part of the phone weighs 5 pounds	
	shall be operable with one hand	Capperts	or more. All operations may be carried	
	and shall not require tight grasping,		out with a single hand with no tight	
	pinching, or twisting of the wrist.		grasping, pinching or twisting required.	
	The force required to activate			
	operable parts shall be 5 pounds			
	(22.2 N) maximum.			
10	07.7 Tickets, Fare Cards, and Keycard	s		
40	Where tickets, fare cards, or	Not Applicable		
	keycards are provided, they shall	Not Applicable		
	have an orientation that is tactilely			
	discernible if orientation is			
	important to further use of the			
	ticket, fare card, or keycard.			
10	<b>17.8 Reach Height and Depth.</b>			
40	At least one of each type of	Supports	VVX phones can be placed on any	
	operable part of stationary ICT	Supports	surface at any position relative to the	
	shall be at a height conforming to			
	407.8.2 or 407.8.3 according to its		user.	
	-			
	position established by the vertical			
	reference plane specified in 407.8.1 for a side reach or a			
	forward reach. Operable parts used			
	with speech output required by			
	402.2 shall not be the only type of			
	operable part complying with			
	407.8 unless that part is the only			
	operable part of its type.			
40	07.8.1 Vertical Reference Plane.			
	Operable parts shall be positioned	Supports	VVX phones can be placed on any	
	for a side reach or a forward reach		surface at any position relative to the	
	determined with respect to a		user.	
	vertical reference plane. The			

All contents copyright © 2018 Polycom, Inc. All rights reserved.

vertical reference plane shall be		
located in conformance to 407.8.2		
or 407.8.3. 407.8.1.1 Vertical Plane for Side Reach		
		VA/V phones can be placed on any
Where a side reach is provided, the	Supports	VVX phones can be placed on any
vertical reference plane shall be 48		surface at any position relative to the
inches (1220 mm) long minimum. 407.8.1.2 Vertical Plane for Forward R		user.
Where a forward reach is provided,		M/V phones can be placed on any
	Supports	VVX phones can be placed on any
the vertical reference plane shall		surface at any position relative to the
be 30 inches (760 mm) long minimum.		user.
407.8.2 Side Reach.	Supports	VA/V shapes can be placed on any
Operable parts of ICT providing a side reach shall conform to	Supports	VVX phones can be placed on any
407.8.2.1 or 407.8.2.2. The vertical		surface at any position relative to the user.
		user.
reference plane shall be centered on the operable part and placed at		
the leading edge of the maximum		
protrusion of the ICT within the		
length of the vertical reference		
plane. Where a side reach requires		
a reach over a portion of the ICT,		
the height of that portion of the		
ICT shall be 34 inches (865 mm)		
maximum.		
407.8.2.1 Unobstructed Side Reach		
Operable parts of ICT providing a	Supports	VVX phones can be placed on any
side reach shall conform to	Supports	surface at any position relative to the
407.8.2.1 or 407.8.2.2. The vertical		user.
reference plane shall be centered		
on the operable part and placed at		
the leading edge of the maximum		
protrusion of the ICT within the		
length of the vertical reference		
plane. Where a side reach requires		
a reach over a portion of the ICT,		
the height of that portion of the		
ICT shall be 34 inches (865 mm)		
maximum.		

All contents copyright © 2018 Polycom, Inc. All rights reserved.

Where the operable part is located more than 10 inches (255 mm), but not more than 24 inches (610 mm), beyond the vertical reference plane, the height of the operable part shall be 46 inches (1170 mm) high maximum and 15 inches (380 mm) high minimum above the floor. The operable part shall not be located more than 24 inches (610 mm) beyond the vertical reference plane.	Supports	VVX phones can be placed on any surface at any position relative to the user.
Operable parts of ICT providing a forward reach shall conform to 407.8.3.1 or 407.8.3.2. The vertical reference plane shall be centered, and intersect with, the operable part. Where a forward reach allows a reach over a portion of the ICT, the height of that portion of the ICT shall be 34 inches (865 mm) maximum.	Supports	VVX phones can be placed on any surface at any position relative to the user.
Where the operable part is located at the leading edge of the maximum protrusion within the length of the vertical reference plane of the ICT, the operable part shall be 48 inches (1220 mm) high maximum and 15 inches (380 mm) high minimum above the floor.	Supports	VVX phones can be placed on any surface at any position relative to the user.
Where the operable part is located beyond the leading edge of the maximum protrusion within the length of the vertical reference plane, the operable part shall conform to 407.8.3.2. The maximum allowable forward reach to an operable part shall be 25 inches (635 mm).	Supports	VVX phones can be placed on any surface at any position relative to the user.
The height of the operable part shall conform to Table 407.8.3.2.1.	Supports	VVX phones can be placed on any surface at any position relative to the user.

Link to table		
Knee and toe space under ICT shall	Not Applicable	
be 27 inches (685 mm) high		
minimum, 25 inches (635 mm)		
deep maximum, and 30 inches (760		
mm) wide minimum and shall be		
clear of obstructions.		
EXCEPTIONS:		
1. Toe space shall be permitted to		
provide a clear height of 9 inches		
(230 mm) minimum above the		
floor and a clear depth of 6 inches		
(150 mm) maximum from the		
vertical reference plane toward the		
leading edge of the ICT.		
2. At a depth of 6 inches (150 mm)		
maximum from the vertical		
reference plane toward the leading		
edge of the ICT, space between 9		
inches (230 mm) and 27 inches		
(685mm) minimum above the floor		
shall be permitted to reduce at a		
rate of 1 inch (25 mm) in depth for		
every 6 inches (150 mm) in height.		

### 408 Display Screens

_				
#	Criteria	Supports	Comments	
4	08.1 General.			
	Where provided, display screens	Not Applicable		
	shall conform to 408.			
4	08.2 Visibility			
	Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be visible from a point located 40 inches (1015 mm) above the floor space where the display screen is viewed.	Not Applicable		
4	408.3 Flashing			

All contents copyright © 2018 Polycom, Inc. All rights reserved.

Where ICT emits lights in flashes, there shall be no more than three flashes in any one-second period.	Not Applicable	
<b>EXCEPTION:</b> Flashes that do not exceed the general flash and red flash thresholds defined in WCAG 2.0 (incorporated by reference, see 702.10.1) are not required to conform to 408.3.		

# **409 Status Indicators**

#	Criteria	Supports	Remarks and comments
4	09.1 General		
	Where provided, status indicators shall be discernible visually and by touch or sound.	Supports	Visual indicators of status such as ringing, on hold, active call etc are displayed on the user interface and also have audible tones associated with them.

# **410 Color Coding**

#	Criteria	Supports	Remarks and comments		
4	410.1 General				
	Where provided, color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	Icons and wording is provided such that color coding is not required. Eg Active call state is indicated by an icon, presence state is indicated by both a colored icon and a text string.		

# **411 Audible Signals**

#	Criteria	Supports	Remarks and comments
4	10.1 General		
	Where provided, audible signals or cues shall not be used as the only means of conveying information, indicating an action, or prompting a response	Supports	A screen flash shall be provided to indicate an incoming call. Other signals (such as call waiting) are also indicated by UX elements on the display. LEDs built into buttons on the phone also provide information on the state of the phone such as incoming or

All contents copyright © 2018 Polycom, Inc. All rights reserved.

		calls that are an hold
		calls that are on hold

All contents copyright © 2018 Polycom, Inc. All rights reserved.

#### 412 ICT with Two-Way Voice Communication

#	Criteria	Supports	Remarks and comments
41	12.1 General		
	Where provided, audible signals or cues shall not be used as the only means of conveying information, indicating an action, or prompting a response	Supports	Information is provided on the display to indicate that there is a call coming in or that a call has been missed.
42	12.2 Volume Gain	1	
	ICT that provides two-way voice communication shall conform to 412.2.1 or 412.2.2.	Supports	
42	12.2.1 Volume Gain for Wireline Tele	phones.	
	Volume gain conforming to 47 CFR 68.317 shall be provided on analog and digital wireline telephones.	Supports	Digital wirelines only.
41	12.2.2 Volume Gain for Non-Wireline	Telephones.	
42	A method for increasing volume shall be provided for non-wireline ICT. 12.3 Interference Reduction and Mag Where ICT delivers output by a	Not Applicable netic Coupling. Supports	All Polycom handsets have primary inductive
	handset or other type of audio transducer that is typically held up to the ear, ICT shall reduce interference with hearing technologies and provide a means for effective magnetic wireless coupling in conformance with 412.3.1 or 412.3.2.		coils that interface with conventional hearing aid pickup, and meet FCC Part 68 requirements for Hearing Aid Compatibility. Polycom VoIP phones meet the FCC Part 68 requirement of a minimum of 12 dB gain range. Additional gain is available via assistive technology amplifiers, such as the Walker Clarity, the Ameriphone HA-40, and the Plantronics EC-225.
41	12.3.1 Wireless Handsets.	ſ	
	ICT in the form of wireless handsets shall conform to ANSI/IEEE C63.19- 2011 (incorporated by reference, see 702.5.1).	Not Applicable	
41	2.3.2 Wireline Handsets.		
	ICT in the form of wireline handsets, including cordless handsets, shall conform to TIA-1083-B (incorporated	Supports	

All contents copyright © 2018 Polycom, Inc. All rights reserved.

	by reference, see702.9.1).		
--	----------------------------	--	--

412.4 Digital Encoding of Speech				
ICT in IP-based networks shall transmit and receive speech that is digitally encoded in the manner specified by ITU-T Recommendation G.722.2 (incorporated by reference, see 702.7.2) or IETF RFC 6716 (incorporated by reference, see 702.8.1).	Supports			
412.5 Real-Time Text Functionality.	[			
Reserved – Note that FCC have				
NOPR for RTT for Wireline IP				
products. Link				
412.6 Caller ID.				
Where provided, caller identification and similar telecommunications functions shall be visible and audible.	Supports With Exceptions	Caller ID is provided on a visual display, but not audibly.		
412.7 Video Communication.	412.7 Video Communication.			
Where ICT provides real-time video functionality, the quality of the video shall be sufficient to support communication using sign language.	Not Applicable			

### 413 Closed Caption Processing Technologies

#	Criteria	Supports	Remarks and comments		
41	413.1 General.				
	Where ICT displays or processes	Not			
	video with synchronized audio, ICT	Applicable			
	shall provide closed caption				
	processing technology that				
	conforms to 413.1.1 or 413.1.2.				
41	L3.1.1 Decoding and Display of Close	d Captions.			
	Players and displays shall decode	Not			
	closed caption data and support	Applicable			
	display of captions.				
42	413.1.2 Pass-Through of Closed Caption Data.				
	Cabling and ancillary equipment	Not			
	shall pass through caption data.	Applicable			

All contents copyright © 2018 Polycom, Inc. All rights reserved.

### 414 Audio Description Processing Technologies.

#	Criteria	Supports	Remarks and comments		
41	414.1 General.				
	Where ICT displays or processes	Not			
	video with synchronized audio, ICT	Applicable			
	shall provide audio description				
	processing technology conforming				
	to 414.1.1 or 414.1.2.				
41	4.1.1 Digital Television Tuners.				
	Digital television tuners shall	Not			
	provide audio description	Applicable			
	processing that conforms to ATSC				
	A/53 Digital Television Standard,				
	Part 5 (2014) (incorporated by				
	reference, see 702.2.1). Digital				
	television tuners shall provide				
	processing of audio description				
	when encoded as a Visually				
	Impaired (VI) associated audio				
	service that is provided as a				
	complete program mix containing				
	audio description according to the				
	ATSC A/53 standard.				

43	414.1.2 Other ICT.			
#	Criteria	Supports	Remarks and comments	
	ICT other than digital television	Not		
	tuners shall provide audio	Applicable		
	description processing.			

#	Criteria	Supports	Remarks and comments		
41	415.1 General				
	Where ICT displays video with synchronized audio, ICT shall provide user controls for closed captions and audio descriptions conforming to 415.1. EXCEPTION: Devices for personal use shall not be required to conform to 415.1 provided that captions and audio descriptions can be enabled through system- wide platform settings.	Not Applicable			
41	15.1.1 Caption Controls				
	Where ICT provides operable parts for volume control, ICT shall also provide operable parts for caption selection.	Not Applicable			
41	15.1.2 Audio Description Controls				
	Where ICT provides operable parts for program selection, ICT shall also provide operable parts for the selection of audio description.	Not Applicable			

#### 415 User Controls for Captions and Audio Descriptions.

All contents copyright © 2018 Polycom, Inc. All rights reserved.